



US009636657B2

(12) **United States Patent**
Bratton et al.

(10) **Patent No.:** **US 9,636,657 B2**
(45) **Date of Patent:** **May 2, 2017**

(54) **HYDRAULICALLY SET CEMENT BODY
FOR PRESERVATION OF ORGANIC
LIQUIDS**

(71) Applicants: **Graham John Bratton**, Kent (GB);
Kenneth George Mannering, Oxford
(GB); **Roger Leslie Brown**, London
(GB); **Neil McNeill Alford**, London
(GB)

(72) Inventors: **Graham John Bratton**, Kent (GB);
Kenneth George Mannering, Oxford
(GB); **Roger Leslie Brown**, London
(GB); **Neil McNeill Alford**, London
(GB)

(73) Assignee: **BBM Technology Ltd**, London (GB)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 747 days.

(21) Appl. No.: **13/661,789**

(22) Filed: **Oct. 26, 2012**

(65) **Prior Publication Data**

US 2013/0112607 A1 May 9, 2013

Related U.S. Application Data

(63) Continuation-in-part of application No. 12/452,984,
filed as application No. PCT/GB2008/050659 on
Aug. 4, 2008, now Pat. No. 8,389,037.

(30) **Foreign Application Priority Data**

Aug. 3, 2007 (GB) 0715096.4

(51) **Int. Cl.**

B01J 20/02 (2006.01)

C04B 28/04 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **B01J 20/02** (2013.01); **A23D 9/00**
(2013.01); **B01J 20/2805** (2013.01);
(Continued)

(58) **Field of Classification Search**

CPC .. **B01J 20/02**; **B01J 20/2805**; **B01J 20/28042**;
C04B 2111/802; **C04B 2111/00284**; **C04B**
38/00; **C04B 28/04**; **B32B 1/02**

See application file for complete search history.

(56)

References Cited

U.S. PATENT DOCUMENTS

1,851,203 A 3/1932 Moreton
3,862,054 A 1/1975 Sokolsky
(Continued)

FOREIGN PATENT DOCUMENTS

GB 2006729 A 5/1979
GB WO 2008015481 A2 * 2/2008 C11B 3/10
(Continued)

OTHER PUBLICATIONS

"U.S. Appl. No. 12/452,984, Non Final Office Action mailed Jul. 6,
2012", 10 pgs.

(Continued)

Primary Examiner — Viren Thakur

(74) *Attorney, Agent, or Firm* — Schwegman Lundberg &
Woessner, P.A.

(57)

ABSTRACT

An hydraulically set oil-permeable cement body is provided
in the form of a stand-alone block or briquette for preserving
cooking oil during deep fat frying, said body. It has sub-
stantially no free water or having a low free water content
for resisting damage on immersion in cooking oil and initial
heating and is enclosed in packaging that resists ingress of
water or water vapor The block or briquette consists of >50
wt % of a mixture of milled white OPC clinker and white
OPC, optionally silica 1-2 wt % and/or titania (TiO₂) 1-2 wt

(Continued)

